

Stingray LED

Modern & stylish quick connect LED Exit Luminaire complete with diffuser and pictogram legend

Specification

- Energy efficient LED
- Quick slide connect installation
- Surface mount Wall/Ceiling
- Maintained or Sustained
- Viewing distance 24M
- Complete one box solution, including diffusers and picto inserts
- Polycarbonate housing and diffuser
- Suitable for both single sided and double side applications

Product Codes

Code	Version	Dim (mm)	Mass (kg)
STTLED	Maint. Theatre LED Exit	395 x 81 x 240	3.0
STLED	Maint. LED Exit	395 x 81 x 240	3.0

Accessories	
99023330	Rod Suspension WH
99023360	Rod Suspension Blk
DIRPPDS	Picto Inserts Double side
DIRPPSS	Picto Inserts Single Side
EXCB	Cantilever Bracket
WGWE	Wall Exit Wire Guard



Quick Specification

Pierlite traditional picto exit with 3W 50,000hr LED module and NiCad batteries. Ceiling or wall mount, Picto inserts included. 24M viewing distance. 17603

Design Application

Commercial office areas, apartment buildings, shopping centres & arcades, cinema's & halls, car parks etc.

Performance

Product Code		Classification	Mounting Height in Metres								
			2.1	2.4	2.7	3	3.6	4	4.5	5	6
STLED	C0	D4	7.2	7.3	7.3	7.3	7.2	6.9	6.5	5.8	3.1
	C90	D3.2	6.5	6.6	6.6	6.5	6.2	5.8	5.1	4.1	
	C180	D4	7.2	7.3	7.3	7.3	7.2	6.9	6.5	5.8	3.1



Picto decals included

IP20



Max Dim (mm)
395 x 81 x 240

PDF Prepared: 15.07.2015 14:07pm, Last page update: Apr 2014

