

LAB T5 Cleanroom

The LAB T5 Cleanroom is designed specifically for cleanroom environments. It is supplied with a torsion spring hinged screw fixed frame and a choice of sealed diffusers above a 3mm clear flat acrylic underlay panel.

Specification

- Powder coated steel body - Torsion spring, screw fixed frame (no screws on request) - Flip out plaster ceiling mounting bracket - Access from below as standard (except bondor type recessed version) - Security version has torx screws and polycarbonate underlay diffuser as option - Surface, plaster recessed, T-bar or bondor type ceiling versions available - 3mm clear flat acrylic underlay panels - Choice of Y12, Y19 and Y5 diffusers - Dimming/Emergency as an option - IP 54 from below - 1.5m flex and 3-pin flat earth plug standard

Product Codes

Code	Version	Mass (kg)
LAB5PN214E5A	LAB T5 2 x 14W Y5 4000K Non Dimmable (Cutout: 584 x 316 x 114)	5.1
LAB5PN214E9A	LAB T5 2 x 14W Y19 4000K Non Dimmable (Cutout: 584 x 316 x 114)	5
LAB5PN228E5A	LAB T5 2 x 28W Y5 4000K Non Dimmable (Cutout: 1184 x 316 x 114)	8.4
LAB5PN228E9A	LAB T5 2 x 28W Y19 4000K Non Dimmable (Cutout: 1184 x 316 x 114)	8.4



Quick Specification

The LAB T5 Cleanroom is designed specifically for cleanroom environments. It is supplied with a torsion spring hinged screw fixed frame and a choice of sealed diffusers above a 3mm clear flat acrylic underlay panel.

Design Application

Clinical areas, Theatres, Critical care units, Research areas, Kitchens, Bathrooms Mounting: T-Bar (lay-in), Plaster flip out brackets, Surface option

Image type unknown

http://www.pierlite.com/data/content/_p.jpg

Performance

IP54



PDF Prepared: 06.02.2017 08:02am, Last page update: Jan 2017

