

# Weatherlux LED

A versatile IP65 LED Picto Exit Luminaire, designed for 16M & 24M viewing distance in compliance with AS/NZ 2293.

## Specification

- Energy efficient lamp LED
- Durable white polycarbonate body with quick connect removable gear tray
- Surface wall or ceiling mount with Pictogram 16m & 24m viewing distance complete polycarbonate diffuser available
- IP65 weatherproof construction
- Removable gear tray
- Tamper proof screws available as an option
- 16M viewing distance for wall mount application
- 24M viewing distance for ceiling mount application

## Product Codes

Code	Version	Dim (mm)	Mass (kg)
WLLED	LED Body Only	368 x 150 x 60	2.5
WLLEDDA	LED DALI Body Only	368 x 150 x 60	2.5

## Accessories

Code	Description	Dim (mm)	Mass (kg)
WL01P	16m Straight from here	365 x 150 x 55	0.3
WL02P	16m Left from here	365 x 150 x 55	0.3
WL03P	16m Right from here	365 x 150 x 55	0.3
WL04P	24m Straight Single Side	365 x 150 x 165	0.5
WL05PL	24m Left Single Side	365 x 150 x 165	0.5
WL06PR	24m Right Single Side	365 x 150 x 165	0.5
WL07DP	24m Double Side	365 x 150 x 165	0.5
WL08DPR	24m Right Double Side	365 x 150 x 165	0.5



## Quick Specification

Pierlite Weatherlux LED Picto Exit, durable white polycarbonate body with quick connect removable gear tray, surface wall mount with pictogram 16M / 24M viewing distance.

## Design Application


Damp environments, warehouses, production facilities, car parks, schools and coastal areas.

## Performance

Wall Mount



Ceiling Mount



IP65



Max Dim (mm)  
365 x 150 x 165

PDF Prepared: 13.10.2017 11:10am, Last page update: Jul 2017

