



AKA TILT

Adjustable LED Downlights Range

AKA blends a mixture of powerful performance with minimalist form critical for harmony within the installed display area. The combination of the “smooth and easy” rotational control is coupled with a constant “clutch” mechanism working in harmony to constantly maintain the optimal tilted position.

AKA TILT

Adjustable LED Downlights Range



Features

- Minimalist profile
- 30° tilt
- Flexibility in design and application
- Constant “clutch” tilt mechanism – remains fixed and droop free but easily adjusted
- Heavy duty mounting springs
- 2 fixed driver outputs
- Dimmable – Dali
- High performance optics reflectors with soft edge illumination & 2 beam choices, 40° & 60°
- Accessories for additional light control
- Low glare
- Protective glass front
- 3000k & 4000k with CRI ≥ 90
- Energy efficient replacement to HID

Applications

- Designed for retail, food preparation and facade

Specifications

	Single
Colour temp	3000K and 4000K
Lumen output	See chart
CRI	>90
Macadams step	3 SDCM
Beam distribution	Symmetric
Default beam angle	40°, 60°
Lumen maintenance	L70 50,000hrs
Control	Remote
Dimensions	Ø186 x H: 124mm
Cutout	Ø175mm
Min recessed depth	154mm
Power factor	0.9
Electrical rating	Class III

AKA TILT

Adjustable LED Downlights Range

Technical Requirements

55/65W	Required Component	
	Driver	65W
	DAT1HF17501	Non-Dim
	DAT1HD17501	DALI
* = Factory Default		

Body selection	Description	Wattage	Lumens Initial	Lumens Exit	mA Setting	Beam Angle	Finishes
AT186317401	AKA TILT 186 65W 3000K 40° REF WHITE	65W	6629	5447	1750mA	40°	Matte White
AT186417401	AKA TILT 186 65W 4000K 40° REF WHITE	65W	7621	6229	1750mA	40°	
AT186317601	AKA TILT 186 65W 3000K 60° REF WHITE	65W	6629	5447	1750mA	60°	
AT186417601	AKA TILT 186 65W 4000K 60° REF WHITE	65W	7621	6229	1750mA	60°	

