

**2015  
WINNER**

— IES NSW —  
**LUMINAIRE  
DESIGN AWARD  
OF EXCELLENCE**



## PIERLITE GENLED ONE LUMINAIRE

The GenLED One luminaire has set the standard in LED luminaires for commercial applications. The innovative design is highly efficient and functional. Designed to create a sustainable and aesthetically pleasing work environment.

# PIERLITE GENLED ONE LUMINAIRE

The GenLED One luminaire was developed with form and function in mind. Low-level side light ambient panels offer a contrast to the main lighting source and give a pleasant ambience to the working environment. It also offers excellent performance and light distribution with the low glare of UGR19 in open office layouts.

## FEATURES

- Excellent performance and light distribution
- Side lit diffused panels
- Available with air handling or blank trim to suit 400mm or 500mm ceilings (on request)
- 60mm shallow body depth
- Colour temperature 4000K CRI 80, SDCM 3
- CRI 90 and other colours on request
- DALI dimmable\*\*
- Easily replaceable remote driver
- Rated average design life 54,000 hours\* L80 B50
- 5 Year system warranty<sup>+</sup>

## BENEFITS




- Highly energy efficient
- Excellent lit appearance
- Aesthetically appealing
- Precise glare control achieves UGR < 19 in office spaces
- Flicker free driver with 7 years warranty

## SPECIFICATIONS

- Sturdy low profile steel body
- Powder coated
- Phosphate pre-treatment
- Acrylic centre and side diffusers
- IP20
- Ta25

## APPLICATIONS

Ideal for Greenstar applications in commercial offices, foyers, medical centres, hospitals and dental surgeries



## PIERLITE GenLED One Luminaire

Product Code	Wattage	Voltage	Lumen	Colour Temp	Dimensions (mm)	Operating Temperature (Max)	Dimmable	Mass (kg)
GLED/1234P	45W	240V	4340 Lm	4000K	D1190 x W290 x H60	25	No	6
GLED/1234U2	45W	240V	4340 Lm	4000K	D1190 x W290 x H60	25	Yes	6
GLED/1234U1	27W	240V	2580 Lm	4000K	D1190 x W290 x H60	25	Yes	6
GLED/1234E	27W	240V	2580 Lm	4000K	D1190 x W290 x H60	25	No	6
GLED/0634U1	13W	240V	1120 Lm	4000K	D590 x W290 x H60	25	Yes	3
GLED/0634U2	24W	240V	2200 Lm	4000K	D590 x W290 x H60	25	Yes	3
GLED/0634E	12W	240V	1120 Lm	4000K	D590 x W290 x H60	25	No	3
GLED/1534U1	35W	240V	3201 Lm	4000K	D1490 x W290 X H60	25	Yes	7

Additional sizes may be available based on your projects requirements.



\*Rated average design life is based on application of PIERLITE's product operating and maintenance guidelines; see [www.gerardlighting.com.au](http://www.gerardlighting.com.au). Actual product life may vary dependent upon frequency of maintenance and product application.\*\* Dimming performance may vary depending on the specifications of the dimmer being used. For best performance we recommend Dignet range.\*Gerard Lighting standard terms and conditions apply.

