

INSTALLATION / WARRANTY INSTRUCTIONS

STARBURST CRYSTAL ECO/STYLE - CRYSECO1, CRYSECO1/10, CRYSECO2, CRYSECO2/10, CRYSECO5, CRYSECO5/10, CRYSECO6, CRYSECO6/10, CRYSECO1/STY, CRYSECO5/STY

PLEASE READ THESE INSTALLATION INSTRUCTIONS CAREFULLY BEFORE INSTALLING OR MAINTAINING THIS EQUIPMENT. THE PRODUCT IS DESIGNED FOR INSTALLATION AND MAINTENANCE IN ACCORDANCE WITH RELEVANT AUSTRALIAN STANDARDS (AS/NZ3000), THESE INSTRUCTIONS AND LOCAL REGULATIONS (WHERE APPLICABLE), BY AN AUTHORISED AND LICENCED ELECTRICIAN.

THE INSTALLATION INSTRUCTIONS WERE CORRECT AT THE TIME OF PRINT. TO REFLECT CHANGES IN TECHNOLOGY AND AUSTRALIAN STANDARDS; PIERLITE AUSTRALIA RESERVES THE RIGHT TO AMEND THE INSTRUCTIONS WITHOUT NOTICE. UPDATED GUIDELINES CAN BE FOUND ON www.pierlite.com.

IMPORTANT - THE PRODUCT MUST BE MAINTAINED AND OPERATED IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS, FAILURE TO DO SO MAY DAMAGE THE PRODUCT AND SERVICES. IT IS STRONGLY RECOMMENDED THAT THIS IMPORTANT NOTE BE COMMUNICATED TO THE OWNER AND OR OPERATOR OF THE INSTALLATION AT THE TIME OF SITE COMMISSIONING. PIERLITE AUSTRALIA IS NOT RESPONSIBLE FOR ANY PRODUCT NOT MAINTAINED IN ACCORDANCE WITH THE RECOMMENDED PROCEDURES.



For the latest product online reference data, simply install and activate a QR code scanner application on your smartphone. For more information visit www.pierlite.com



1. PRODUCT SPECIFICATION:

Type of Protection	- Class II
IP Rating	- IP20 (Style options up to IP54 see carton)
Nominal Voltage	- 240V
Circuit wattage	- 11W
Line current	- 50mA
Power factor	- 0.95
Nominal Freq. (Hz)	- 50 Hz
Rated Maximum Ambient Temperature	- 50°C
Suitable for direct mounting on flammable surfaces	- YES
Dimmable (if relevant refer www.pierlite.com for approved list)	- YES
Installation orientation	- Recessed in a horizontal interior position.
Designed application	- Residential & commercial interiors

2. APPROVALS: The RCM marking of this product applies to AS/NZS CISPR15:2006 (EMC) "Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment". This product is designed to conform to AS/NZS60598 "Luminaires, general requirements and tests".



3. STORAGE: Prior to installation products are to be stored in cool and dry conditions.

4. APPLICATION: The installation application and orientation of the product is designed in accordance with the nominated product IP rating, class designation and these installation installations. Installation environments outside these conditions are not recommended.

5. INSTALLATION / GENERAL: Installation of the product is to be completed by an authorized and licenced electrician, in accordance with these instructions, relevant Australia standards and local regulations (where applicable). All cable terminations must be installed in accordance with the designated IP rating of the product. **For electronic control equipment (when supplied) DO NOT MEGGER between A and N.**

6. INSTALLATION / SPECIAL CONDITIONS (relevant only for products approved for such an installation):

(a) products installed in high wind environments not applicable

(b) Products installed in corrosive or salt laden environments require special consideration and such; specific product selection, inclusive of suitable fastening methods and extensive ongoing maintenance of products installed in these environments require professional advice. It is essential that all aspects of the product selection, material specification and maintenance are specifically designed for such use.

(c) Interior Highbay products not applicable

(d) Interior (downlight) products must be installed to ensure the lamp unit or the driver are not covered with any combustible materials or insulation; minimum spacings nominated for these materials are mandatory. Unless otherwise specified, a minimum clearance of 100mm is required above and 25mm around the luminaire from all standard building trusses. The product is not designed for installation environments which restrict conventional airflow movements eg: enclosed boxes or concrete profiles. For dimming purposes please see the relevant product brand web site for the dimming compatibility chart. When mounting multiple fixtures to conductive structures, it is recommended that the structure is earthed. The mounting facilities provided for the transformer/driver (if any), need only be utilized if in the application of the product is required by AS/NZS3000. IP ratings stated (if any) are from below the ceiling unless stated otherwise and the installation of the product must be in a manner that maintains the integrity of the relevant IP rating. **(e)** The starburst Crystal ECO is designed with a multifunction downlight profile suitable for either 92mm or 70mm cut-outs. For 92mm cut-outs the three positioning posts on the top side of the downlight should be simply snapped off prior to installation.

7. MAINTENANCE: The supply must be isolated before opening or accessing the luminaire. Product maintenance is IMPORTANT and is critical to the products designed performance. The product is to be maintained in accordance with the manufacturer's instructions. For the latest product maintenance guides please go to www.pierlite.com. Pierlite Australia is not responsible for any product not maintained in accordance with the recommended procedure or intervals.

(a) lamps (where provided): The product is designed with the supplied (LEDs) / lamp/s and it is strongly recommended that any lamp / (LEDs) changes (if any) be made in accordance with the type, colour and brand supplied. For recommended LAMP / LED maintenance or operating guides (inclusive of switch cycles), Pierlite Australia recommends the application of the lamp manufacturer's operating guidelines, which can be found on manufacturer's website. Pierlite Australia is not responsible for the product performance of alternative lamp/s used. As a member of FluroCycle, Pierlite Australia encourages recycling of lamps and components.

(b) Battery (where provided): The battery is designed with a rated average battery design life of 25,000 hrs in standby mode. The battery is supported with a standard 12 month warranty; conditional of the product being maintained and operated in accordance with the manufacturer's guidelines and tested in accordance with AS/NZS2293. For guidelines see product installation instructions or visit www.pierlite.com.

(c) For products supplied with glass visors or covers, do not operate the product with a damaged visor or cover; it is recommended the product be turned off, area surrounding the product vacated and the damaged glass replaced by a professional installer immediately.

8. Warranty components - Pierlite Starburst Crystal ECO , Starburst Crystal ECO style, (identified as the driver and LED lamp unit only) **Warranty period** - The above components are provided with a warranty of three (3) years against manufacturing defects or failure to perform to specifications for products installed by an authorized installer in accordance with the manufacturer's installation instructions and which have not been subject to incorrect operation or maintenance, unauthorized modification or damage arising from any intervening cause. Warranty reference - The warranty reference date commences from the date of purchase. Warranty point of contact - Pierlite Australia Pty Ltd, 96 Gow Street Padstow NSW 2211, phone +61 2 9794 9300, email lighting@pierlite.com.au, contact - Pierlite After Sales Support. Warranty claim procedure - For the purpose of making a claim the customer must: 1. Contact the "point of contact" above and upon provision of proof of purchase the customer will receive a goods return advice (GRA) number. 2. At the customer's expense, collect and return the goods to the "point of contact" with the issued GRA number. 3. Upon receipt of the goods, Pierlite Australia will review the claim and if found to be accepted, Pierlite Australia will return a replacement product to the customer to install at the customer's expense. Alternatively if the claim is rejected, the customer may request the return of the goods at their expense. Consumer Contracts - The benefits to the customer given by the Pierlite Australia warranty are in addition to other rights and remedies of the customer if the goods are the subject of a Consumer Contract under the Australian Consumer Law. In that event the following statement is required to be brought to the Consumer's attention :-Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Limitation of Liability - if the goods are not purchased by the customer under a Consumer Contract within the Australian Consumer Law then but not otherwise;-

a) The Company is not liable in tort for any loss or damage suffered by the customer or by any third party; and
b) in no circumstances is Pierlite Australia liable to the customer or to any third party for any loss of profits, loss of anticipated savings, economic loss or interruption of business or for any indirect or consequential loss.

Terms of Sale - these Warranty provisions are in substitution for any inconsistent provisions in the Pierlite Australia Terms and Conditions of Sale in so far as they apply to the Warranty components.