

OLYMPIC HID FLOODLIGHT



Disano Olympic IP65 flat glass cut-off asymmetric floodlight in coated die-cast aluminium to suit double ended long-arc lamps with remote control ear assembly.



Pressure die-cast alum. body coated with polyester resin based powder paint, resistant to corrosion/saline environments



Asymmetric reflector in high purity anodized and polished aluminium



Heavy duty mounting bracket laquered in black (with 3 x 22mm dia holes for flexibility)



Tempered 4mm thick safety glass resistant to thermal shock



Rear opening door with stainless steel latches for easy lamp access and maintenance



Integral power supply disconnecting switch



Adjustable lamp position to obtain four different photometric distributions



Ignitor included in box attached to trunnion arm, remote control gear assemblies required, hot restrike option

OLYMPIC HID FLOODLIGHT

Product Specification

3000 Rated Average Life	IP65 IP Rating	18KG Mass (kg)	4000K Colour Temperature	Powdercoated Finish
HID (Metal Halide) Lamp Type	.23 Windage	Asymmetric Beam Distribution	-5 to 40 Operating Temperature	90 Tilt

Item Code	Description	System Power (W)	Voltage
415211-49XNB2	OLYMPIC 2KW C/W M2000T10/DE 240V FUSED G/B BIRD PROOF	2290W	240V
415211-49XNP4	OLYMPIC 2KW C/W M2000T10/DE 415V FUSED G/T BIRD PROOF	2256W	415V
415211-49XNB4	OLYMPIC 2KW C/W M2000T10/DE 415V FUSED G/B BIRD PROOF	2256W	415V
415211-49SP1	OLYMPIC OL/BP 1808 2KW OSR LMP C/W BIRD PROOF COND N/LP&GEAR	2290W	240V

LINE DRAWINGS

