





IP 20



- Corpo in estruso verniciato, lunghezza 600 mm.
- Gruppo di alimentazione integrato.
- Main body made of extruded aluminium, length 600 mm.
- Built-in power supply unit.

SIDESIGN

DROP 60 XS	LED	SISTEMA-SYSTEM						
		W	lm	V	K	CRI	W	lm
Br D2213-LBC Ne D2214-LBC Ga D2215-LBC	3,5W 285	220-240V (350mA)	3000	>80	4,5W	257	57	200,00
Br D2213-LBN Ne D2214-LBN Ga D2215-LBN	3,5W 300	220-240V (350mA)	4000	>80	4,5W	287	64	200,00



DROP 60 M	LED	SISTEMA-SYSTEM						
		W	lm	V	K	CRI	W	lm
Br D2225-MLBC-25 D2225-MLBC-40 Ne D2226-MLBC-25 D2226-MLBC-40 Ga D2227-MLBC-25 D2227-MLBC-40	6,1W 610	220-240V (350mA)	3000	>80	7,1W	610	86	215,00
Br D2225-MLBN-25 D2225-MLBN-40 Ne D2226-MLBN-25 D2226-MLBN-40 Ga D2227-MLBN-25 D2227-MLBN-40	6,1W 660	220-240V (350mA)	4000	>80	7,1W	611	86	215,00



DROP 60 XL	LED	SISTEMA-SYSTEM						
		W	lm	V	K	CRI	W	lm
Br D2237-LBC-15 D2237-LBC-25 D2237-LBC-40 Ne D2238-LBC-15 D2238-LBC-25 D2238-LBC-40 Ga D2239-LBC-15 D2239-LBC-25 D2239-LBC-40	17W 2500	220-240V (500mA)	3000	>80	20	2262	113	310,00
Br D2237-LBN-15 D2237-LBN-25 D2237-LBN-40 Ne D2238-LBN-15 D2238-LBN-25 D2238-LBN-40 Ga D2239-LBN-15 D2239-LBN-25 D2239-LBN-40	17W 2665	220-240V (500mA)	4000	>80	20	2367	118	310,00




OP. A richiesta - On request: Led con temperatura di **COLOre 2700k** - Temperature Led **COLOur 2700k**

OP. A richiesta - On request: Finitura Bronzo e Oro - Bronze and Gold fi



DATIFOTOMETRICI - PHOTOMETRIC DATA



(m)	∅ (m)		(lx)	
Alpha= 96°-96°	Beta= 10°-10,7°	max	med	
1.0	0,34	0,38	9436	6185
2.0	0,68	0,76	2359	1546
3.0	1,02	1,14	1048	687
4.0	1,36	1,52	590	387
5.0	1,70	1,90	377	247