



AKA MINI

Adjustable LED Downlights Range

AKA blends a mixture of powerful performance with minimalist form critical for harmony within the installed display area. The combination of the “smooth and easy” rotational control is coupled with a constant “clutch” mechanism working in harmony to constantly maintain the optimal tilted position.

AKA MINI

Adjustable LED Downlights Range



Features

- Minimalist profile
- Multidirectional 355° rotation 55° tilt
- Flexibility in design and application
- Constant “clutch” tilt mechanism – remains fixed and droop free but easily adjusted
- Heavy duty mounting springs
- 3000k & 4000k with CRI ≥ 90
- Dimmable – Dali, 1-10v
- High performance optics reflectors with soft edge illumination & 3 beam choices, 20° 40° & 60°
- Accessories for additional light control
- Low glare

Applications

- Designed for retail and commercial applications

Specifications

	Single
Colour temp	3000K and 4000k
Lumen output	See chart
CRI	>90
Macadams step	3 SDCM
Beam distribution	Symmetric
Default beam angle	20°, 40°, 60°
Lumen maintenance	L70 50,000hrs
Control	Remote
Dimensions	Ø108 x H:82mm
Cutout	Ø100mm
Min recessed depth	112mm
Power factor	0.9
Electrical rating	Class III

Option

AK108RN20	Narrow 20°
AK108RM40	Medium 40°
AK108RW60	Wide 60°

AKA MINI

Adjustable LED Downlights Range

Technical Requirements

15W	Required Component	
	Driver	15W
	DAD20F03501	Non-Dim
	DAD20D03501	DALI
	DAD20V035001	1-10V
* = Factory Default		

Body selection	Description	Wattage	Lumens Initial	Lumens Exit	mA Setting	Finishes
AK108331	AKA MINI 15W 3000K NO REF WHITE	15W	1231	932	350mA	Matte White Matte Black
AK108431	AKA MINI 15W 4000K NO REF WHITE	15W	1351	996	350mA	
AK108332	AKA MINI 15W 3000K NO REF BLACK	15W	1231	932	350mA	

