



SWITCHBLADE

LED Track Spot light range

The Switchblade provides first class options for display applications, designers and architects looking for superior flexibility in an LED accent lighting system. The Switchblade variable offers a wide range of focus from 25° all the way to 60°, highlighting any valuable area or object.

SWITCHBLADE

Range of LED Trackspots



Features

- A sleek, cylindrical design
- Foldable design
- Real 2 in 1 flexible fixture
- Beam angle range 24° to 60°
- 360° rotatable track head
- Track head pivots through to 90°
- The Switchblade's flexible head means that it can be used in a wide variety of positions and applications.
- Variable lens gives a project a more accurate result
- Each project can be specifically tailored and adjusted when merchandise is re-arranged
- Inline driver reduces heat, extending the product's life span

Key Applications

- Residential
- Retail
- Museums
- Exhibitions
- Galleries
- Show room areas

Specifications

Colour Temp	3000K
Lumen Output	See Chart
CRI	93+
Macadams Step	3 SDCM
Beam Distribution	Symmetric
Default Beam Angle	24° / Variable
Lumen Maintenance	L70 50,000hrs
Control	Integrated
Dimensions	Ø76mm x H:185mm
Mounting	3C Universal Track Adaptor
Power Factor	0.9
Electrical Rating	Class II

SWITCHBLADE

Range of LED Trackspots

Technical Requirements

Body Selection	Description	Colour Temp	mA Factory Default Setting	Lumens Initial	Lumens Exit	Wattage	CRI	Life / L70	Track Compatability
SB763370241	SWB L3 25W 24° 3K WH	3000K	700	2086	1912	25	90+	50,000	Staff 3C Erco 3C Nordic 3C Eutrack 3C Global 3C Ivela 3C
SB763370242	SWB L3 25W 24° 3K BL	3000K	700	2086	1912	25	90+	50,000	
SB763370VA1	SWB L3 25W VAR FOC 25°-60°3K WH	3000K	700	2003	1908	25	90+	50,000	
SB763370VA2	SWB L3 25W VAR FOC 25°-60°3K BL	3000K	700	2003	1908	25	90+	50,000	

