

# Suspended luminaire

VIVAA C 400 (DALI) D15647000-00678091



<b>fitted with</b>	4 x LED - Energy efficiency category A+
<b>light distribution</b>	direct/indirect
<b>color rendering index (CRI)</b>	> 80
<b>colour temperatur</b>	4000 K
<b>work equipment</b>	electronic converter
<b>mains lead</b>	direct power supply
<b>luminaire body</b>	stainless steel
<b>weight (net)</b>	4.3 kg
<b>Power consumption</b>	54 W
<b>luminous flux</b>	5300 lm
<b>luminous efficacy</b>	0 lm/W
<b>lamp cover</b>	CDP micro prismatic screen (PMMA) continuously dimmable
<b>class of protection</b>	I
<b>norms</b>	EN 60598-1, EN 60598-2-25
<b>Room height</b>	270 - 300 cm, ceiling clearance 50 cm
<b>special features</b>	Suitable for screen work according to EN 12464-1, CDP micro prismatic screen, DALI version, Suitable for emergency lighting units according to EN 50172
<b>Fastening</b>	ceiling fastening (pendel)
<b>Glare-free</b>	prismatic screen
<b>System of protection</b>	IP 20
<b>order number</b>	D15647000 - Stainless steel/pure white

## light distribution

