



<b>fitted with</b>	4 x LED module - Energy efficiency category A+
<b>light distribution</b>	General light indirect 43 W, lighting for reading direct 10 W, night lighting indirect 3 W, examination lighting direct 60 W
<b>color rendering index (CRI)</b>	> 80 & > 90
<b>colour temperatur</b>	4000 K / 3000 K / 2700 K
<b>work equipment</b>	electronic converter
<b>mains lead</b>	direct power supply
<b>luminaire body</b>	aluminium
<b>weight (net)</b>	6.9 kg
<b>Power consumption</b>	122 W
<b>luminous flux</b>	10890 lm
<b>luminous efficacy</b>	89 lm/W
<b>lamp cover</b>	PMMA clear, PMMA satined single switchable
<b>class of protection</b>	I
<b>norms</b>	EN 60598-1, EN 60598-2-25
<b>special features</b>	general lighting & night light 3000 K, lighting for reading 2700 K, night lighting, Switch for examination light left, Low voltage circuit breaker (LVC), examination light 4000 K, examination light CRI >90
<b>Fastening</b>	wall mount
<b>Glare-free</b>	freeform optic
<b>System of protection</b>	IP 20
<b>order number</b>	D15939000 - aluminium (anodised)

## light distribution

