



## AKA MINOR

### *Adjustable LED Downlights Range*

AKA blends a mixture of powerful performance with minimalist form critical for harmony within the installed display area. The combination of the “smooth and easy” rotational control is coupled with a constant “clutch” mechanism working in harmony to constantly maintain the optimal tilted position.

# AKA MINOR

## Adjustable LED Downlights Range



### Features

- Minimalist profile
- Multidirectional 355° rotation 70° tilt
- Flexibility in design and application
- Constant “clutch” tilt mechanism – remains fixed and droop free but easily adjusted
- Heavy duty mounting springs
- 3000k & 4000k with CRI ≥ 90
- Dimmable – Dali, 1-10v
- High performance optics reflectors with soft edge illumination & 3 beam choices, 20° 40° & 60°
- Accessories for additional light control
- Low glare
- Protective glass front
- Energy efficient replacement to HID

### Applications

- Designed for retail, food preparation and facade

### Specifications

	Single
Colour temp	3000K and 4000k
Lumen output	See chart
CRI	>90
Macadams step	3 SDCM
Beam distribution	Symmetric
Default beam angle	20°, 40°, 60°
Lumen maintenance	L70 50,000hrs
Control	Remote
Dimensions	Ø152 x H:130mm
Cutout	Ø143mm
Min recessed depth	160mm
Power factor	0.9
Electrical rating	Class III

# AKA MINOR

## Adjustable LED Downlights Range

### Technical Requirements

30W	Required Component		
	Driver		30W
	DAD32F07001	Non-Dim	700mA*
	DAD32D07001	DALI	
	DAD32V07001	1-10V	
* = Factory Default			

Body selection	Description	Wattage	Lumens Initial	Lumens Exit	mA Setting	Beam Angle	Finishes
AK152370201A	AKA MINOR 30W 3000K 20° REF WHITE	30W	2373	1922	700mA	20°	Matte Black Matte White
AK152470201A	AKA MINOR 30W 4000K 20° REF WHITE	30W	2552	2067	700mA	20°	
AK152370202A	AKA MINOR 30W 3000K 20° REF BLACK	30W	2373	1922	700mA	20°	
AK152470202A	AKA MINOR 30W 4000K 20° REF BLACK	30W	2552	2067	700mA	20°	
AK152370401A	AKA MINOR 30W 3000K 40° REF WHITE	30W	2373	1922	700mA	40°	
AK152470401A	AKA MINOR 30W 4000K 40° REF WHITE	30W	2552	2067	700mA	40°	
AK152370402A	AKA MINOR 30W 3000K 40° REF BLACK	30W	2373	1922	700mA	40°	
AK152470402A	AKA MINOR 30W 4000K 40° REF BLACK	30W	2552	2067	700mA	40°	
AK152370601A	AKA MINOR 30W 3000K 60° REF WHITE	30W	2373	1922	700mA	60°	
AK152470601A	AKA MINOR 30W 4000K 60° REF WHITE	30W	2552	2067	700mA	60°	
AK152370602A	AKA MINOR 30W 3000K 60° REF BLACK	30W	2373	1922	700mA	60°	
AK152470602A	AKA MINOR 30W 4000K 60° REF BLACK	30W	2552	2067	700mA	60°	

# AKA MINOR

## Adjustable LED Downlights Range

### Technical Requirements

