

Solid



- Corpo in pressofusione di alluminio.
- Verniciatura in polveri con pretrattamento speciale per esterni.
- Schermo in policarbonato opale.
- Guarnizioni in gomma silicónica.

- Die-cast aluminium body.
- Powder coated with pretreatment for outdoor use.
- Polycarbonate diffuser screen.
- Gasket in silicone rubber.
- 50,000 rated average design life*

	W	lm	V	K
TUTTO SCHERMO - FULL SCREEN				
Br E5385-LBC	19,4W	2320	220-240V	3000
Ne E5386-LBC				
Gr E5387-LBC				
<hr/>				
Br E5385-LBN	19,4W	2440	220-240V	4000
Ne E5386-LBN				
Gr E5387-LBN				
<hr/>				
DOPPIA ACCENSIONE - DOUBLE LIGHTING				
Br E5393-LBC	21W	2320		
Ne E5394-LBC	(18W)*+ (3W)**	(1933)*+ (386)**	220-240V	3000
Gr E5395-LBC				
*accensione 1 - lighting 1 **accensione 2 - lighting 2				
<hr/>				
DOPPIA ACCENSIONE - DOUBLE LIGHTING				
Br E5393-LBN	21W	2440		
Ne E5394-LBN	(18W)*+ (3W)**	(2033)*+ (406)**	220-240V	4000
Gr E5395-LBN				
*accensione 1 - lighting 1 **accensione 2 - lighting 2				

CON PALPEBRA - WITH EYELID				
Br E5390-LBC	19,4W	2320	220-240V	3000
Ne E5391-LBC				
Gr E5392-LBC				
<hr/>				
Br E5390-LBN	19,4W	2440	220-240V	4000
Ne E5391-LBN				
Gr E5392-LBN				
<hr/>				
DOPPIA ACCENSIONE - DOUBLE LIGHTING				
Br E5396-LBC	21W	2320		
Ne E5397-LBC	(18W)*+ (3W)**	(1933)*+ (386)**	220-240V	3000
Gr E5398-LBC				
*accensione 1 - lighting 1 **accensione 2 - lighting 2				
<hr/>				
DOPPIA ACCENSIONE - DOUBLE LIGHTING				
Br E5396-LBN	21W	2440		
Ne E5397-LBN	(18W)*+ (3W)**	(2033)*+ (406)**	220-240V	4000
Gr E5398-LBN				
*accensione 1 - lighting 1 **accensione 2 - lighting 2				



5 year warranty

*Rated average design life is in accordance with IEC standards. Actual product life may vary dependent upon frequency of maintenance and product application.